

Trailer		
Length	31' 4" - 34' 9"	9.55 m - 10.59 m
Width	8'	2.4 m
Height	11' 2"	3.39 m
Storage space **	23' 6" x 5' 9" x 5' 8"	7.2 m x 1.8 m x 1.7 m
Storage Compartment	18" x 18" x 16"	0.46 x 0.45 x 0.41 m
Storage space capacity **	5,000 lb	2,268 kg
Weight	9,990 lb	4,531 kg

Stage Floor		
Length and Depth	24' x 20'	7.3 x 6.1 m
Length and Depth with Extension Platforms	40' x 24'	12.2 x 7.3 m
Height	3' 6" to 4' 3"	1.07 to 1.30 m
Design Live Load	100 lb/ft ²	490 kg/m ²
Type of Surface	Plywood on aluminium	

Roof		
Length and Depth	24' 11" x 23' 9"	7.59 x 7.23 m
Clearance (Inclined roof)	13' 9" to 14' 7"	4.22 to 4.45 m
Maximum Height with Banner*	23' 8"	7.21 m
Type of Surface	Fibreglass bonded on aluminium	
Roof Lifting Capacity	3,800 lb	1,725 kg
Roof Load Bearing Capacity	6,500 lb	2,948 kg
4 Built in Rigging Points	350 lb each	160 kg each
2 Trusses - Upstage and Downstage (T2)	500 lb	227 kg
2 Trusses - Central Roof (T1)	700 lb each	320 kg each
2 Front Overhang Extensions - 9' 10" (3 m)*	250 lb at 34" each	113 kg at 0.86 m each
2 Side Overhang Beams	800 lb at 36" each	363 kg at 0.9 m each

Practical Aspects	
Installation Time Once Levelling Complete	30 minutes - Less without windwall
Personnel Required	1 Certified technician and 1 stagehand
Site Preparation	None
Heavy Machinery Required	None
Mode of Transportation	1 Pick-up truck or fifth-wheel tractor*
Gust Wind Resistance	60 mph (97 km/h) with windwall or 80 mph (129 km/h) without windwall
Promotional Visibility*	Rolling billboard, multiple banner options
Rigging Bars*	Retractable, can be loaded from ground or stage level
Windwall*	Weatherproof - fire retardant vinyl or scrim (blow-through material)
Vertical and Horizontal Banner Supports*	Installed at ground level, close to 340 ft ² (31.6 m ²) of promotional space
Floor Extension Platforms*	Integrated brackets - easy to install